SEMC 2022: The eighth international conference on Structural Engineering, Mechanics and Computation, Cape Town, South Africa, 5-7 Sep 2022

# Bolted and hybrid beam-column joints between I-shaped FRP profiles

Paper Reference: SEMC 2022-226 Session Reference: E-W2-8

Dr Jawed Qureshi (Presenting author) Senior Lecturer at University of East London, London, United Kingdom

Dr Yashida Nadir Associate Professor, College of Engineering Trivandrum, Kerala India

Dr Shaise K John Research scholar, College of Engineering Trivandrum, Kerala India

Dr J Qureshi – J.Qureshi@uel.ac.uk; Dr Y Nadir – Yashidanadir@cet.ac.in; Dr S K John -shaisekjohn25@gmail.com



Pioneering Futures Since 1898


# OUTLINE

- Background
- Test arrangement
- Test results
- Failure modes
- Conclusions



# Background






FRP profiles

FRP rebars

Dr Jawed Qureshi - J.Qureshi@uel.ac.uk





#### FRP strengthening



# Background

# Dawlish bridge Davon UK

All composite FRP footbridge spanning a coastal railway line




Old rusty steel bridge reconstructed in 1937

New All-FRP bridge 2011 – **no corrosion** 

Dr Jawed Qureshi - J.Qureshi@uel.ac.uk



#### Test arrangement



Schematic diagram – single cantilever test set up


Dr Jawed Qureshi - J.Qureshi@uel.ac.uk




Photograph of beam-column sub-assembly




# Test arrangement – joint detailing




1. SFSc2: Bolted steel cleats



4. SFStc2A: Hybrid steel flange cleats




2. SFSc2A: Hybrid steel cleats



5. SFFc2: Bolted FRP cleats


Dr Jawed Qureshi - J.Qureshi@uel.ac.uk



3. SFStc2: Bolted steel flange cleats



# Test arrangement – Loading protocol Cyclic loading history



SAC protocol (SAC 1997)

Dr Jawed Qureshi - J.Qureshi@uel.ac.uk


Reviewed loading protocols (Filiatrault *et al*. 2018)

ATC-24 and SAC for steel structures ISO and CUREE for wooden structures FEMA-461 and FM-1950 for nonstructural elements

SAC loading protocol is used



# Joints with steel web and flange cleats




1. SFSc2: Bolted joint with steel web and flange cleats 2. SFSc2A: Hybrid joint with steel web and flange cleats

Dr Jawed Qureshi - J.Qureshi@uel.ac.uk

Monotonic test results are from a paper by the authors <u>https://doi.org/10.1016/j.compstruct.2020.112500</u>.




# Joints with steel flange cleats only



4. SFStc2A: Hybrid joint with steel flange cleats only



# Joint with FRP web and flange cleats




**Joint rotation (mrad)** 

5. SFFc2: Bolted joint with FRP web and flange cleats

Dr Jawed Qureshi - J.Qureshi@uel.ac.uk



# Cyclic performance



Accumulated dissipated energy of each joint against number of cycles


Dr Jawed Qureshi - J.Qureshi@uel.ac.uk

- Dissipated energy of hybrid joints is 75% higher than bolted joints
- Dissipated energy FRP joints is half of steel joints
- Energy performance of web and flange cleated and flange cleated and flange cleated only joints is similar



### Failure modes

# Shear-out failure at beam's bolted zone



1. SFSc2: Bolted joint with steel web and flange cleats



3. SFStc2: Bolted joint with steel flange cleats only

Dr Jawed Qureshi - J.Qureshi@uel.ac.uk



### Failure modes

# Adhesive debonding with shear-out failure



2. SFSc2A: Hybrid joint with steel web and flange cleats

Dr Jawed Qureshi - J.Qureshi@uel.ac.uk



4. SFStc2A: Hybrid joint with steel flange cleats only



# Failure modes Delamination cracking







5. SFFc2: Bolted joint with FRP web and flange cleats

Dr Jawed Qureshi - J.Qureshi@uel.ac.uk





# Conclusions

- Three failure modes: shear-out, debonding and delamination
- Hybrid joints showed twice as much stiffness as bolted joints
- Dissipated energy of hybrid joints is 75% higher than bolted joints
- Dissipated energy of FRP joints is about half of steel joints
- Adding web cleat to a flange cleated joint offers no benefit
- Bonding delays initiation of damage in FRP cleats and members

nding and delamination tiffness as bolted joints 5% higher than bolted

ut half of steel joints oint offers no benefit h FRP cleats and members



# Ongoing work

# PFC-RHS and RHS-RHS beam-to-column joints



Courtesy of Access Design and Engineering UK

Cooling Tower system (Courtesy of Creative Composites USA)

Dr Jawed Qureshi - J.Qureshi@uel.ac.uk



# References

Qureshi J, Nadir Y, John SK. 2020. Bolted and bonded FRP beam-column joints with semi-rigid end conditions. Compos Struct. 247:112500.

SAC. 1997. Protocol for Fabrication, Inspection, Testing and Documentation of Beam- column Connections and Other Experimental Specimens. Report No. SAC/BD-97/02, SAC Joint Venture Sacramento, CA.

Filiatrault A, Perrone D, Brunesi E, Beiter C, Piccinin R. 2018. Effect of cyclic loading protocols on the experimental seismic performance evaluation of suspended piping restraint installations. Int J Press Vessel Pip. 166:61–71.

Dr Jawed Qureshi - J.Qureshi@uel.ac.uk



# Thanks for listening.....Questions?

#### A recent review paper:

Qureshi J. 2022. A Review of Fibre Reinforced Polymer Structures. Fibers. 10(3):27.



A copy of this presentation is available at <u>bit.ly/SEMC2022-JQ</u>

#### **Dr Jawed Qureshi**

- Website: <a href="https://www.bit.ly/UEL-JQ">bit.ly/UEL-JQ</a>
- Email: J.Qureshi@uel.ac.uk
- Phone: +44 208 223 2363

#### Research

- bit.ly/ResearchGate-JQ
- bit.ly/Googlescholar-JQ
- bit.ly/ORCID-JQ

#### Social

- bit.ly/twitter-JQ
- <u>bit.ly/Linkedin-JQ</u>



